

PMD660

Continued from previous page

Exclusive-"Virtual Track" Mode

For more sophisticated editing jobs, the PMD660 features Marantz Professional's exclusive "Virtual Track" mode. In this mode, you can create up to 99 virtual tracks-internal playlists of audio segments. You simply tell the PMD660 what segments of a file to play, and in what order, and it does it-without altering the original file in any way, and without using up more card memory. Need 5 and 10 second sound bites and a two-minute interview segment, all from the same file? It's easy with virtual tracks.

Optional Wired Remote

It would be great if every recording situation had a field engineer running everything behind the scenes. Unfortunately, all too often it's just you, wishing you had more hands. The RC600 wired remote control enables you to start and stop recording, and to mark new track-starts on the fly. It even has a peak meter right on the remote, so you can keep an eye on your recording, without taking your eye off the ball.



The optional RC600 Mic Remote attaches directly onto your favorite handheld mic and gives you full record control with peak indication.



D&M Professional
1100 Maplewood Drive Itasca, Illinois 60143
Tel: 630.741.0330 Fax: 630.741.0652
www.d-mpro.com

Specifications

Digital Audio System

System	Solid State Recorder
Usable media	CF memory card Microdrive
Recording format	
MP3	MPEG Audio Layer III compression
PCM	16 bit linear PCM
Recording bit rate	
MP3 mono	64 kbps
MP3 stereo	128 kbps
Sampling frequency	44.1, 48 kHz
Number of channels	2 (stereo), 1 (mono)

Audio Performance

Frequency response	16,000 Hz (-0.5dB)
Signal-to-noise ratio	LINE 80 dB
IEC-A weighted	MIC 60 dB
Total harmonic distortion	LINE 0.06%
at 0 VU (PCM)	MIC 0.15%
Dynamic range	80 dB

Inputs

MIC IN L/R	
Type	XLR (1:GND, 2:HOT, 3:COLD)
Input sensitivity	1.2 mV rms /6.5k ohms
LINE IN L/R	
Type	1/8" mini jack
Input sensitivity	300 mV rms /20k ohms

Outputs

LINE OUT L/R	
Type	1/8" mini jack
Standard level	2 V rms max. /2k ohms
Headphone	
Type	1/8" mini jack
Output power	8 mW /32 ohms
Speaker	
Output power	150 mW /16 ohms
Phantom power	+48V, 5mA

General

Power consumption	4 W (DC)
Recording/Playback	
Battery life (Alkaline)	4 Hours (typical)
Dimensions	
Width	4.5" (113 mm)
Height	1.9" (47 mm)
Depth	7.2" (183.5 mm)
Weight	1.1 lbs. (0.5 kg)

Included Accessories

CF card (64MB) (US only)	1
AC adapter	1
USB cable	1
Audio cable	1
Carry strap	1
Screws (ISO 3x10 mm)	2
Plastic pin and retainer	1
CD-ROM	1
User guide	1

Optional Accessories

Wired remote	RC600PMD
--------------	----------

(See www.d-mpro.com for description and/or ordering information)

PLEASE NOTE: Specifications are based on measurement conditions and proper care for the machine and are subject to change without notice.

© 2005 ULM Professional. All rights reserved.

DENON
PROFESSIONAL

marantz
PROFESSIONAL

1 2 3 4 5 6 7 8 9
min | max
LEVEL